


# Series 1 Filter / Regulators


**Features:**

- particle removal per ISO 8573-1, Class 5 and Class 3
- pressure range 5-150 PSI
- in-line or modular installation
- 40 micron element
- 2 oz. reservoir
- quick-release bayonet bowl


- prismatic lens liquid level indicator
- supplied with GC620 gauge
- inlet pressure:
  - transparent bowl: **150 PSI** at ambient temperature (70°F)
  - metal bowl: **250 PSI** at ambient temperature (70°F)




1/4 Turn Manual Drain  
\*\* minimum clearance required to remove bowl




Semi auto Drain  
\*\* minimum clearance required to remove bowl




1/4 Turn Manual Drain  
\*\* minimum clearance required to remove bowl



Automatic Drain  
\*\* minimum clearance required to remove bowl



Manual Drain  
\*\* minimum clearance required to remove bowl



Automatic Drain  
\*\* minimum clearance required to remove bowl

## Sub-Compact with Transparent Bowl

Port Size	Flow (SCFM)	Semi-Automatic Drain		Manual Drain	
		Part #	Price/E	Part #	Price/E
1/4"	80	<b>B72G-2AG</b>	<b>\$204.30</b>	<b>B72G-2MG</b>	<b>\$142.05</b>
3/8"	80	<b>B72G-3AG</b>	<b>207.65</b>	<b>B72G-3MG</b>	<b>146.80</b>

## Sub-Compact with Metal Bowl and Sight Glass

Port Size	Flow (SCFM)	Semi-Automatic Drain		Manual Drain	
		Part #	Price/E	Part #	Price/E
1/4"	80	<b>B72G-2AG-MB</b>	<b>\$218.45</b>	<b>B72G-2MG-MB</b>	<b>\$157.95</b>
3/8"	80	<b>B72G-3AG-MB</b>	<b>222.50</b>	<b>B72G-3MG-MB</b>	<b>161.70</b>

**Features:**

- particle removal per ISO 8573-1, Class 5 and Class 3
- pressure range 5-150 PSI
- in-line or modular installation
- 40 micron element
- 3.5 oz. reservoir
- quick-release bayonet bowl

- prismatic lens liquid level indicator
- supplied with GC230 gauge
- inlet pressure:
  - transparent bowl: **150 PSI** at ambient temperature (70°F)
  - metal bowl: **250 PSI** at ambient temperature (70°F)

## Compact with Transparent Bowl

Port Size	Flow (SCFM)	Automatic Drain		Manual Drain	
		Part #	Price/E	Part #	Price/E
1/4"	78	<b>B73G-2AG</b>	<b>\$288.30</b>	<b>B73G-2MG</b>	<b>\$215.45</b>
3/8"	123	<b>B73G-3AG</b>	<b>288.30</b>	<b>B73G-3MG</b>	<b>215.45</b>
1/2"	123	<b>B73G-4AG</b>	<b>288.30</b>	<b>B73G-4MG</b>	<b>215.45</b>

## Compact with Metal Bowl and Sight Glass

Port Size	Flow (SCFM)	Automatic Drain		Manual Drain	
		Part #	Price/E	Part #	Price/E
1/4"	78	<b>B73G-2AG-MB</b>	<b>\$297.50</b>	<b>B73G-2MG-MB</b>	<b>\$224.65</b>
3/8"	123	<b>B73G-3AG-MB</b>	<b>294.85</b>	<b>B73G-3MG-MB</b>	<b>224.65</b>
1/2"	123	<b>B73G-4AG-MB</b>	<b>297.50</b>	<b>B73G-4MG-MB</b>	<b>221.70</b>

**Features:**

- pressure range 5-125 PSI
- 40 micron element
- 7 oz. reservoir
- relieving type

- supplied with GC230 gauge
- inlet pressure:
  - transparent bowl: **150 PSI** at ambient temperature (70°F)
  - metal bowl: **250 PSI** at ambient temperature (70°F)

## Standard with Transparent Bowl and Guard

Port Size	Flow (SCFM)	Automatic Drain		Manual Drain	
		Part #	Price/E	Part #	Price/E
3/8"	163	<b>B74G-3AG</b>	<b>\$342.35</b>	<b>B74G-3MG</b>	<b>\$266.55</b>
1/2"	212	<b>B74G-4AG</b>	<b>339.40</b>	<b>B74G-4MG</b>	<b>263.05</b>
3/4"	212	<b>B74G-6AG</b>	<b>339.40</b>	<b>B74G-6MG</b>	<b>264.20</b>

## Standard with Metal Bowl and Sight Glass

Port Size	Flow (SCFM)	Automatic Drain		Manual Drain	
		Part #	Price/E	Part #	Price/E
3/8"	163	<b>B74G-3AG-MB</b>	<b>\$347.30</b>	<b>B74G-3MG-MB</b>	<b>\$271.30</b>
1/2"	212	<b>B74G-4AG-MB</b>	<b>339.60</b>	<b>B74G-4MG-MB</b>	<b>267.70</b>
3/4"	212	<b>B74G-6AG-MB</b>	<b>372.90</b>	<b>B74G-6MG-MB</b>	<b>267.70</b>

See page 260 for filter/regulator accessories.



FRL's are designed for air service only, unless otherwise indicated.

SCFM ratings given at 150 PSIG inlet pressure.



with transparent bowl



with metal bowl



with transparent bowl



with metal bowl



with guard



with metal bowl